

Datasheet for three-phase Squirrel-Cage-Motors

Order Number: 1LE0101-1DC43-4AB4

Client-order-no.:

Order-no.:

Offer-no.:

Remarks:

Item-no.:

Consignment-no.:

Project:



Electrical data

| | |
|-------------------------|--------------------------------|
| Rated motor voltage: | 400VD / 690VY |
| Frequency: | 50 Hz |
| Rated motor power: | 11 kW |
| Rated motor speed: | 965 1/min |
| Maximum Speed: | 2400 1/min |
| Number of poles: | 6 |
| No load current: | 10.7 A |
| Rated current: | 23 A |
| Starting current: | 6.6 |
| Rated motor torque: | 109 Nm |
| Torque class: | K |
| Starting torque: | 2.2 |
| Breakdown torque: | 3.1 |
| Efficiency class: | IE 2 |
| Efficiency 100% Load: | 88.7% |
| Efficiency 75% Load: | 89.4% |
| Efficiency 50% Load: | 89.5% |
| Power factor 100% Load: | 0.78 |
| Motor protection: | 3 PTC thermistors for tripping |
| Terminal box position: | terminal box on top |

Mechanical data

| | |
|--------------------------------------|-------------------------|
| Noise (Lpfa): | 60.00 dB(A) |
| Moment of inertia: | 0.077 kg m ² |
| Cantilever force for x0: | 3750 N |
| Cantilever force for xmax: | 2900 N |
| Bearing drive end: | 6309 2Z C3 |
| Bearing non-drive end (hor.mount.): | 6209 2Z C3 |
| Bearing non-drive end (vert.mount.): | 6209 2Z C3 |
| Drain holes: | yes |
| Regreasing device: | no |
| Relubrication interval at 40°C: | |
| Coating: | RAL 7030 stone gray |

Site conditions

| | |
|-------------------------------|------------------|
| Ambient temperature: | -20.0°C to +40°C |
| Altitude above sea level: | 1000m |
| Standards and specifications: | IEC |

General data

| | |
|------------------------|--------------------------|
| Frame size: | 160L |
| Type of construction: | IMB3 |
| Weight in kg (net): | 132 kg |
| Frame material: | Cast iron |
| Fan cover material: | metal |
| Degree of protection: | IP 55 |
| Method of cooling: | Self-ventilated (IC 411) |
| Vibration class: | A (standard) |
| Insulation: | 155(F) / 130(B) |
| Duty type: | S1 = cont. operation |
| Direction of rotation: | bidirectional |

Terminal box

| | |
|----------------------------------|-----------------------|
| Material of terminal box: | Cast iron |
| Terminal screw thread: | M5 |
| Max. cable cross-sectional area: | 16 mm ² |
| Cable diameter from ... to ...: | 22 - 32 mm |
| Cable entry: | M40 x 1.5 + M40 x 1.5 |
| Cable gland: | no |

Explosion protection

| | |
|---------------------|--------------------|
| Type of protection: | without (standard) |
|---------------------|--------------------|

Special configurations

Technical and ordering data are subject to change. There may be discrepancies between calculated and rating plate values.

Printed on 2013-02-08