

Datasheet for three-phase Squirrel-Cage-Motors

Order Number: 1LE0101-2DC23-4AB4

Client-order-no.:

Order-no.:

Offer-no.:

Remarks:



Item-no.:

Consignment-no.:

Project:

Electrical data

Rated motor voltage:	400VD / 690VY
Frequency:	50 Hz
Rated motor power:	55 kW
Rated motor speed:	986 1/min
Maximum Speed:	1800 1/min
Number of poles:	6
No load current:	34.5 A
Rated current:	101 A
Starting current:	7.5
Rated motor torque:	533 Nm
Torque class:	K
Starting torque:	2.4
Breakdown torque:	2.7
Efficiency class:	IE 2
Efficiency 100% Load:	93.1%
Efficiency 75% Load:	93.7%
Efficiency 50% Load:	93.6%
Power factor 100% Load:	0.85
Motor protection:	3 PTC thermistors for tripping
Terminal box position:	terminal box on top

Mechanical data

Noise (Lpfa):	65.00 dB(A)
Moment of inertia:	1.5 kg m ²
Cantilever force for x0:	9650 N
Cantilever force for xmax:	8120 N
Bearing drive end:	6317 C3
Bearing non-drive end (hor.mount.):	6317 C3
Bearing non-drive end (vert.mount.):	7317 AC
Drain holes:	yes
Regreasing device:	yes
Relubrication interval at 40°C:	5000 h
Coating:	RAL 7030 stone gray

Site conditions

Ambient temperature:	-20.0°C to +40°C
Altitude above sea level:	1000m
Standards and specifications:	IEC

General data

Frame size:	280M
Type of construction:	IMB3
Weight in kg (net):	535 kg
Frame material:	Cast iron
Fan cover material:	metal
Degree of protection:	IP 55
Method of cooling:	Self-ventilated (IC 411)
Vibration class:	A (standard)
Insulation:	155(F) / 130(B)
Duty type:	S1 = cont. operation
Direction of rotation:	bidirectional

Terminal box

Material of terminal box:	Cast iron
Terminal screw thread:	M10
Max. cable cross-sectional area:	120 mm ²
Cable diameter from ... to ...:	37 - 44 mm
Cable entry:	M63 x 1.5 + M63 x 1.5
Cable gland:	no

Explosion protection

Type of protection:	without (standard)
---------------------	--------------------

Special configurations

Technical and ordering data are subject to change. There may be discrepancies between calculated and rating plate values.

Printed on 2013-02-08